POLYGUM® · FURNITURE GRADE · CODE PG-HM-SAFW

# POLYGUM® Hot Melt SAFW

## SPECIMEN: format and acceptance limits only

Every batch is tested by our QC laboratory and ships with a signed COA showing its actual results. For the COA of a batch you received, email marketing@synergybonding.in with the batch number on the pack. Limits per PS/PG-HM-SAFW/R02. Not valid as a certificate for any batch.

## Batch Details

| | | | |
|---|---|---|---|
| **Product / code** | POLYGUM® Hot Melt SAFW (PG-HM-SAFW) | **Batch no.** | |
| **Customer** | | **Date of manufacture** | |
| **Invoice / PO no.** | | **Best before** | |
| **Pack size** | | **Quantity** | |

## Test Results

| Parameter | Specification | Test method | Result |
|---|---|---|---|
| Colour | Frosty white | Visual | |
| Viscosity | 50,000 ± 15,000 cP at 190°C | Brookfield Thermosel viscometer at the stated temperature | |
| Density | 1.3 – 1.35 g/cm³ | Displacement method | |
| Softening point | 100 ± 5°C | Ring and ball | |

## Conclusion

| | |
|---|---|
| **QC remarks** | |
| **Result** | The batch conforms / does not conform to the specification above. |

**QC In-charge**
Name, signature and date

**Approved by**
Name, signature, date and stamp

SPECIMEN