

SYNERGY BONDING SOLUTIONS PVT. LTD.

(An ISO 9001:2015 Company)

Manufacturers and Exporters of Packaging Adhesives

H.O: Off No-25/26, 4th Floor, Highway Towers, Chinchwad, Pune - 411019, India

www.synergybonding.in

Email ID: marketing@synergybonding.in

Technical Data Sheet

Product Name: “POYGUM” DISHLAM 15

No: TDS/DISHLAM 15/2018

Date: Oct 10, 2018

DISHLAM 15 is an Acrylic aqueous dispersion developed for packaging industries.

Characteristics:

Appearance	: Clear Colorless Liquid
Polymers type	: Dispersion
Solid content (%)	: 14.00 – 16.00
Brook field Viscosity (cPs)	: 7000 – 10000 (RVDV-E Sp 5/20)
Ph	: 2.00 – 4.00

Properties & Applications:

“POLYGUM” DISHLAM 15 is specially developed for paper dish making manual & machine application, also recommended primarily for paper to paper, Paper to foils, paperboard to paperboard pasting.

Storage & Handling

“POLYGUM” DISHLAM 15 can be stored in poly lined or plastic drums. To have a longer shelf life the container should be kept tightly closed in cool but frost free place. The product can be easily washed off with water before the film dries up. In some case warm water with little scrubbing is required. In the event of the product coming in the direct contact with eyes or skin washing with plenty of water should be restored. For any abnormal symptoms seek medical advice

Stability

“POLYGUM” DISHLAM 15 has a long shelf life of 6 month provided it is stored in cool place.

Packing

“POLYGUM” DISHLAM 15 is available in 50 Kgs.

Disclaimer:

These suggestion and data are based on information we believe to be reliable. They are offered in good faith, but without guarantee, as condition and methods of use of our products are beyond our control. We recommend that the prospective user(s) determine the suitability of our materials and suggestions before adopting then on commercial Scale.

Life Long Bond