



OMBOND-EB

Extra Bonding

Product description:

Ready to use, Higher Coverage, Fast Drying, High Bonding Strength

Ombond "EB" is a Extra Bonding synthetic resin adhesive intended for wood working and various materials where one of the surfaces to be bonded is porous. Ombond Extra Bonding strongly binds wood, plywood, laminate, veneers, MDF and all types of boards.

Areas of Application:

- Plywood to Laminate
- Hot Press / Cold Press
- Manual Pressing
- Other general purposes

Application Methods:

- Surfaces to be bonded should be free from oil, grease, and dust and dirty.
- Should be dry and properly leveled.
- For best results, roughen the surfaces to be bonded.
- Stir content of container before use.
- Apply even coats of OMBOND EB first on comparatively on porous surface for e.g. apply first on porous surface like plywood, MDF, particle board.
- Do not allow adhesive to dry, and bring both the surfaces in contact together, make proper alignment and start pressing from one side by using wet squeezed cloth to avoid bubbles, and ensuring uniform contact and no air interruption between both the surfaces.
- Pressure can be given using nails, clamps, weight, masking tape etc.

Product Features:

- Excellent compatibility with Plywood and Lamination
- High Strength with long & durable bonding
- Excellent Spread ability and High Coverage
- Excellent heat resistance

Product Benefits:

- Best Solution for fixing lamination sheets
- Helpful
- Good for Lamination
- Saves Cost
- Excellent for heat prone applications like kitchen or high temperature climatic zones.

Technical Specification

Solid Content	44(±2%)
Viscosity (RVT/SP-6/20/30°C)	200 – 300 Poise
PH value	4-6
Free Monomer (%)	0.3 Max
Coverage (under standard conditions)	50 – 55 Sq. ft. / kg

Pack size

250g, 500g, 1kg, 5kg, 10kg, 30kg & 50kg



Head Office:

Synergy Bonding Solutions Pvt Ltd

Office No. 24 & 25, 4th Floor, Highway Towers, Pune-Mumbai Road, Chinchwad, Pune - 411 019

Email: marketing@synergybonding.in

Customer Care: +91 9371 63 5315