



OMBOND

Membrain Adhesive

Product description:

Made out of excellent quality material, the Ombond Membrane Press Adhesive offers you the binding quality that holds for a very long time. This is a good quality product that comes in a all type of packaging size and can be used in a large amount of industries. The adhesive is mainly used for handling the purposes of vacuum press and membrane machinery.

Areas of Application:

- PVC Foil to MDF Board

Application Methods:

- Surfaces to be bonded should be free from oil, grease, and dust and dirty.
- Should be dry and properly leveled.
- For best results, roughen the surfaces to be bonded.
- Stir content of container before use.
- Apply even coats of Membrain Adhesive first on comparatively on porous surface for e.g. apply first on porous surface like plywood, MDF, particle board.
- Do not allow adhesive to dry, and bring both the surfaces in contact together, make proper alignment and start pressing from one side by using wet squeezed cloth to avoid bubbles, and ensuring uniform contact and no air interruption between both the surfaces.
- Pressure can be given using machine or vacuum press, machine as per standard.

Product Features:

- Single Component
- Low heat activation
- Used in membrane and vacuum press machines
- Excellent heat resistance
- Excellent spread availability and high coverage

Product Benefits:

- It is easy to applying and job thru spraying
- Saves cost
- Good adhesive strength

Technical Specification

Solid Content	52% (±2%)
Viscosity (RVT/SP – 6/20/30°C)	80 – 130 Poise
Application	Spray
PH value	2-3
Free Monomer (%)	0.3 Max
Coverage (under standard conditions)	45 – 50 Sq. ft. / kg

Pack size

5kg, 10kg, 30kg, 50kg



Head Office:

Synergy Bonding Solutions Pvt Ltd

Office No. 24 & 25, 4th Floor, Highway Towers, Pune-Mumbai Road, Chinchwad, Pune - 411 019

Email: marketing@synergybonding.in

Customer Care: +91 9371 63 5315