



OMBOND-WP

Water Proof Adhesives

Product description:

Heat Resistance, Water Proof bond, High Coverage, fast Drying

Weather change and continuous exposure to water and moisture expose furniture to stress. This could result in opening of joints and de-bonding of laminates in spite of using good quality material. 'Ombond Waterproof Adhesives' is a specialized waterproof adhesive that protects furniture from de-bonding even when exposed to water.

Areas of Application:

- Bonds laminate, plywood and other hard /soft wood, veneer, particle board, MDF, block board, hard board, etc
- Specially made for the handicraft industry and bonds all types of wood and ply to laminate, mainly in areas where furniture is affected by moisture/water like kitchens, bathrooms, etc.

Application Methods:

- Surfaces to be bonded should be free from oil, grease, and dust and dirty.
- Should be dry and properly leveled.
- For best results, roughen the surfaces to be bonded.
- Stir content of container before use.
- Apply even coats of OMBOND EB first on comparatively on porous surface for e.g. apply first on porous surface like plywood, MDF, particle board.
- Do not allow adhesive to dry, and bring both the surfaces in contact together, make proper alignment and start pressing from one side by using wet squeezed cloth to avoid bubbles, and ensuring uniform contact and no air interruption between both the surfaces.
- Pressure can be given using nails, clamps, weight, masking tape etc.

Product Features:

- 2 hrs. boiling waterproof, 72 hrs. normal waterproof
- High Strength cross linking Adhesive
- Excellent Spread ability and High Coverage
- Excellent heat resistance

Product Benefits:

- Save Cost
- Spread Easily
- Better Coverage
- Best Solutions for fixing
- Laminate, Plywood, Veneer, Matt any wood to wood bonding.
- Particle Board, Block Board to Laminate
- Excellent for heat prone applications like kitchen or high temperature climatic zones

Technical Specification

Solid Content	45% ($\pm 2\%$)
Viscosity (RVT/SP – 6/20/30°C)	150-250 Poise
PH value	3-5
Free Monomer (%)	0.3 Max
Coverage (under standard conditions)	50 – 55 Sq. ft. / kg

Pack size

250g, 500g, 1kg, 5kg, 10kg, 30kg & 50kg



Head Office:

Synergy Bonding Solutions Pvt Ltd

Office No. 24 & 25, 4th Floor, Highway Towers, Pune-Mumbai Road, Chinchwad, Pune - 411 019

Email: marketing@synergybonding.in

Customer Care: +91 9371 63 5315