



OMCOL

Product description:

Low cost adhesive. Mainly used for readymade furniture making and wood filling application.

Areas of Application:

- For mica pressing 0.8 mm.
- For wood filling.
- General purpose.

Application Methods:

- Surfaces to be bonded should be free from oil, grease, and dust and dirty.
- Should be dry and properly leveled.
- For best results, roughen the surfaces to be bonded.
- Stir content of container before use.
- Apply even coats of OMBOND Omcol first on comparatively on porous surface for e.g. apply first on porous surface like plywood, MDF, particle board.
- Do not allow adhesive to dry, and bring both the surfaces in contact together, make proper alignment and start pressing from one side by using wet squeezed cloth to avoid bubbles, and ensuring uniform contact and no air interruption between both the surfaces.
- Pressure can be given using nails, Clamps, Weight, masking tape etc.

Product Features:

- Excellent compatibility with Plywood and Lamination
- Moderate Strength with long and durable bonding
- Excellent Spread ability and High Coverage

Product Benefits:

- Good for Lamination
- Cost Saver
- General purpose adhesive for Non-critical Jobs.

Technical Specification

Solid Content	25% ($\pm 2\%$)
Viscosity (RVT/SP – 6/20/30°C)	200 – 300 Poise
Application	Manual
PH value	6-8
Free Monomer (%)	0.3 Max
Coverage (under standard conditions)	40 – 42 Sq. ft. / kg

Pack size

1kg, 5kg, 50kg



Head Office:

Synergy Bonding Solutions Pvt Ltd

Office No. 24 & 25, 4th Floor, Highway Towers, Pune-Mumbai Road, Chinchwad, Pune - 411 019

Email: marketing@synergybonding.in

Customer Care: +91 9371 63 5315