

polygum[®]

Multi Purpose



“ VALUE FOR MONEY ADHESIVE ”

**Furniture
Packaging Industries
Handicraft**

PRODUCT DESCRIPTION : Ready to use, Higher Coverage, Fast Drying, High Bonding Strength
POLYGUM “MP” is a Multi Purpose synthetic resin adhesive intended for wood working and various materials where one of the surfaces to be bonded is porous. POLYGUM “MultiPurpose” strongly binds wood, plywood, laminate, veneers, MDF and type of boards.

Areas Of Application:

- Plywood to Laminate
- Hot Press / Cold Press
- Manual Pressing
- Other general purposes

Application Methods:

- Surfaces to be bonded should be free from oil, grease, and dust & dirty.
- Should be dry and properly leveled.
- For best result, roughen the surfaces to be bonded.
- Stir content of container before use.
- Apply even coats of “polygum MP” first on comparatively on porous surface for e.g. apply first on porous surface like plywood, MDF, particle board.
- Do not allow adhesive to dry and bring both the surfaces in contact together make proper alignment & start pressing from one side by using wet squeezed cloth to avoid bubbles and ensuring uniform contact and no air interruption between both the surfaces.
- Pressure can be given using nails, clamps, weight, masking tape etc.

Product Features :

- Excellent compatibility with Plywood and Lamination.
- High strength with long & durable bonding.
- Excellent Spread ability and High Coverage.
- Excellent heat resistance.

Product Benefits :

- Best solution for fixing Lamination sheets
- Helpful For Lamination
- Good for Lamination
- Saves cost
- Excellent for heat prone applications like kitchen or high temperature climatic zones.

Technical Specification

VISCOSITY (RVT/SP-6/20/30C) 180 – 250 Poise	
PH value	4 – 6
Free Monomer (%)	0.3 Max
Coverage	50-55 Sq. ft / kg
(Under Standard Conditions)	

Pack Size

250g, 500g, 1kg, 5kg, 10kg, 30kg & 50kg



Head Office:

Synergy Bonding Solutions Pvt Ltd

Office No.24 & 25, 4th Floor, Highway Towers, Pune-Mumbai Road, Chinchwad Pune-411019.

Email: marketing@synergybonding.in

Customer Care: +91 9371635315

www.synergybonding.in